



Barra Sextavada Trefilada		
Bitola	Tolerância	Peso Nominal
h (mm)	(mm)	(kg/m)
6,35	+0/-0,09	0,270
7,94	+0/-0,09	0,430
9,53	+0/-0,09	0,620
11,11	+0/-0,11	0,840
*12,70	+0/-0,11	1,086
*14,29	+0/-0,11	1,378
*15,88	+0/-0,11	1,704
*17,46	+0/-0,11	2,062
19,05	+0/-0,13	2,470
20,64	+0/-0,13	2,900
22,22	+0/-0,13	3,360
23,81	+0/-0,13	3,850
24,00	+0/-0,13	3,920
25,40	+0/-0,13	4,390
26,99	+0/-0,13	4,950
28,58	+0/-0,13	5,550
30,00	+0/-0,13	6,120
31,75	+0/-0,16	6,850
33,34	+0/-0,16	7,560
34,92	+0/-0,16	8,290
36,00	+0/-0,16	8,810
38,10	+0/-0,16	9,870
41,28	+0/-0,16	11,580
42,86	+0/-0,16	12,490
44,45	+0/-0,16	13,430
50,80	+0/-0,19	17,540

*Bitolas produzidas com cantos arredondados - Barras de 6m
Fornecida de acordo com a Norma SAE 1020/1045.

