



## Tubos Quadrados - Laminados a Quente

Peso Teórico (kg/6 mts)

Bitola		Espessura da Parede											
		1,20	1,50	1,80	2,00	2,25	2,65	3,00	3,35	3,75	4,00	4,25	4,75
Pol.	mm	BQ	BQ	BQ	BQ	BQ	BQ	BQ	BQ	BQ	BQ	BQ	BQ
3/4"	15x15	3,17	3,90		5,05								
1"	20x20	4,30	5,30	6,29	6,92	7,71	8,92	9,94					
1.1/4"	25x25	5,42	6,71	7,98	8,80	9,82	11,41	12,76	14,08				
1.1/2"	30x30	6,55	8,12	9,67	10,68	11,93	13,90	15,58	17,22	19,06			
1.3/4"	35x35	7,68	9,53	11,36	12,56	14,05	16,39	18,40	20,37	22,58			
2"	40x40	8,81	10,94	13,05	14,44	16,16	18,88	21,22	23,52	26,11	27,70	29,27	32,36
2.1/4"	45 x 45				16,36	18,33	21,43	24,10					
2.1/2"	50x50	11,06	13,76	16,43	18,20	20,39	23,86	26,85	29,81	33,15	35,21	37,26	41,29
3"	60x60	13,32	16,58	19,81	21,96	24,62	28,84	32,49	36,11	40,20	42,73	45,24	50,22
3.1/2"	70x70	15,57	19,40	23,20	25,72	28,85	33,82	38,13	42,40	47,25	50,25	53,23	59,14
4"	80x80	17,90	22,30	26,69	29,59	33,21	38,95	43,94	48,90	54,51	58,00	61,47	68,35
5"	100 x 100				37,00	42,53	48,76	55,04	61,29	68,39	72,65	77,19	85,92

\* Norma ABNT 6591, Material SAE 1006 e 1012